

wd40.co.uk / wd40.ie

Scan to find out more

SPECIALIST CONTACT CLEANER







- Drives out surface contaminants that can cause current leakage, corrosion or component failure.
- Removes moisture and condensation for better electrical contact.
- Non-conductive spray with dielectric strength of 33.8 kV.

MATERIALS: Electrical contacts, incidental contact with plastic and rubber.

APPLICATIONS: Circuit boards, switches, spark plugs, smoke alarms.



HARD TO Reach Places



COMPONENTS



NO RESIDUE



TEMPERATURE RANGE
Use at room temperature





wd40.co.uk / wd40.ie

Scan to find out more

<u>Specialist</u> Penetrant







- Breaks down rust to loosen seized parts.
- Provides a protective, water resistant film to prevent further rust or corrosion.
- Ouickly saturates deep into seams, crevices and threads.

MATERIALS: Metal, stainless steel, titanium, rubber, plastic, PVC.

APPLICATIONS: Seized nuts, bolts & fixings, locks, chains, hinges, pulleys.



PENETRATES RUST



LOOSENS SEIZED







TEMPERATURE RANGE -20°C to +90°C



HEAVY
DUTY
GREASE
THAT
STICKS
AROUND

THERE'S A SPECIALIST FOR THAT

wd40.co.uk / wd40.ie

Scan to find out more



SPECIALIST WHITE LITHIUM GREASE







- Protects heavy-duty, metal-to-metal connections.
- Heat and water resistant, so can be used outdoors in any weather conditions.
- High viscosity formula that won't drip or run.

MATERIALS: Metal, stainless steel, titanium. APPLICATIONS: Bearings, winches, conveyors, latches, tracks & runners.



REDUCES FRICTION









LONG LASTING SPRAY GREASE THAT DOESN'T

THERE'S A SPECIALIST FOR THAT

wd40.co.uk / wd40.ie

Scan to find out more

SPECIALIST SPRAY GREASE





SPRAY GREASE



- · Long-lasting lubrication and corrosion protection.
- Non-drip formula that uses WD-40 MUP as base of the formula.
- Strong adhesion and sealing properties to lubricate constantly moving parts.

USE ON

MATERIALS: Metal, stainless steel, titanium, rubber, plastic, PVC.

APPLICATIONS: Gear mechanisms, chains, locks, screws, pipes, taps.









TEMPERATURE RANGE Grease -20°C to +115°C, liquid to +260°C



FRICTION
FREE CUTTING
OIL FOR
LONGER
LASTING

THERE'S A SPECIALIST FOR THAT

TOOLS

wd40.co.uk / wd40.ie

Scan to find out more

SPECIALIST.
CUtting oil







- Improves machine finishes on cutting and drilling eauipment.
- Prevents overheating, pitting, tip wielding and metal seizures.
- Spray format allows for mess-free application and easy clean up.

MATERIALS: Metal, stainless steel. Not suitable for titanium. APPLICATIONS: Hand cutting machinery, drill bits & drilling equipment, tapping equipment, power drills.



ANTI-WEAR



WON'T ATTRACT







FAST DRYING SILICONE FOR QUICK MOVING JOBS

THERE'S A SPECIALIST FOR THAT

wd40.co.uk / wd40.ie

Scan to find out more

PECIALIST.
SILICONE







- Creates water resistant seal to protect against moisture.
- Reduces friction and wear to prevent cracking and ageing.
- Provides excellent lubrication particularly on rubbers, plastics and PVC.

MATERIALS: Metal, stainless steel, titanium, rubber, plastic, PVC, wood.

APPLICATIONS: Belts, conveyors, door runners, door seals, windows.



RUST & CORROSION



STICKING




& PROTECTS



TEMPERATURE RANGE -35°C to +200°C.





wd40.co.uk / wd40.ie

Scan to find out more

<u> BPECIALIST</u> De<mark>greas</mark>er







- Quickly removes stubborn oil, grease, dirt and grime to reduce wear & tear.
- · Solvent-based spray format allows for mess-free application and easy clean up.
- NSF K1 registered, so can be used in non-processing areas.

MATERIALS: Metal, stainless steel, titanium. APPLICATIONS: Engines, power tools, industrial machinery. gear mechanisms.








NO RESIDUE



TEMPERATURE RANGE Use at room temperature





wd40.co.uk / wd40.ie



SPECIALIST DRY LUBRICANT







- Enhanced lubrication and corrosion protection.
- · Leaves a dry, clear film that won't attract dirt, dust or oil.
- Water-resistant formula that reduces wear & tear.

MATERIALS: Metal, stainless steel, titanium, glass, plastic, PVC.

APPLICATIONS: Locks, latches, pliers, window tracks, conveyor belts, metal extrusions.





LUBRICATES



TEMPERATURE RANGE -45°C to +90°C

