

# WD-40 SPECIALIST®

## BIO LUBRICANT MULTI-USE

DATA  
SHEET

### PRODUCT OVERVIEW

WD-40 SPECIALIST® Bio Lubricant MULTI-USE consists of a 85% bio-based formula, with a cap made from >50% recycled plastic. WD-40 SPECIALIST® Bio Lubricant MULTI-USE can be used on metals, plastics, and rubber. The EU Ecolabel certification supports usage inside the home, as well as in workshops and the garden.



EU Ecolabel: IT/027/010

### FEATURES & BENEFITS

- Multi-Use Performance
- 85% bio-based formula
- Reduces friction & wear
- Pressure-resistant
- Penetrates
- Displaces moisture
- Protects against corrosion
- Ecolabel certified

### RECOMMENDED FOR

The product works to provide lubrication, protection and maintenance for various applications, such as home maintenance, automotive care, power tools and machinery maintenance.

### DIRECTIONS FOR USE

Shake can well before use. For best results do not wipe away. Disconnect power tools, appliances, and other live electrical sources before spraying. If required, remove with Mineral spirits, lacquer thinners, vapour degreasing or alkaline cleaner.



Appearance/Colour	Brown
Odour	Characteristic
Specific Gravity (20!C)	0.89 - 0.93 g/cm3
Discharge Rate	TBC
NSF Category & Number	H2 (#172391)
Flammability	High Flammable (Category 1) Aerosol
Flashpoint	181.5oC
Salt Spray ASTM B117	30% after 48h
Dielectric Strength ASTM D-877	30 000V per 1 inch
4 Ball Wear ASTM D4172	0.68 - 0.75 mm
Surface Tension ASTM D1331	17-18 dynes/cm
Water Displacement FTM 3007	0 - 5 %
Extreme Pressure ASTM D3233	1500- 1600 lb
Viscosity ASTM D445	8.78 cSt at 40°C
Water Content	<0.4%
Bio content ASTM D6866 Method B	85% biogenic carbon
Temperature range	up to 100°C